



PRODUCT TECHNICAL DATA SHEET

Canister K-10 SOR

BASIC DATA

Nominal Capacity:	10 L	Application:	industrial chemistry
Thread Standards:	FI 63		household chemistry
Material Options:	HDPE ≥ 97% / dye ≤ 3%		agro sector

AVAILABLE VARIANTS

Parameter	Value	Certificates	Visibility Strip:	available
Weight:	420 g	UN (II i III, to 1,6 g/cm³)	Touch Sign:	available
Colors:	white, gold, other to be agreed with our employee		IML Label:	not available
Seal Type:	foam-PE		Printing:	not available
			Customer Logo:	available
			Seal Type:	not available
			Thread Type:	Ø63

DIMENSIONS

Parameter	Value	Notes	Parameter	Value	Notes
Weight:	420 g	±10 g	Length:	230 mm	±3 mm
Label Area:	180(H) x 180(W) mm		Width:	166 mm	±2,5 mm
			Height:	380 mm	±4,5 mm

AVAILABLE CLOSURES

K 63 NS AUTOMATYKA 5-8 Nm

PALLETIZATION AND STORAGE - EMPTY PACKAGES

Packaging System No.:	ST24P144	Pallet:	1200x800 mm
Label Content:	manufacturer's name, production date	Spacers:	cardboard trays
	product type, product quantity (pcs)	Pallet Module:	6 layers, stretch foil
	batch number, quality mark	Quantity per layer:	24 pcs
Storage:	protect against sunlight and weather conditions	Quantity per pallet:	144 pcs
	min. 1m away from heat sources	Pallet Weight:	85 kg
	ambient temperature up to 40°C	Pallet Height:	2,5 m
Shelf Life:	12 months from delivery	Seasoning before Filling:	min. 10 h at temp. 16-25°C
Filling Temperature:	max. 40°C		

TRANSPORT - EMPTY PACKAGES

Transport:	protection against rain, deformation, contamination and shifting
Warning:	additional loading of transport modules is not permitted
Layer Arrangement:	



STORAGE AND TRANSPORT - FILLED PACKAGING

Completing:	The packaging manufacturer recommends stacking filled canisters in a maximum of three layers, using cardboard dividers on each layer. Completed filled canisters should be wrapped in stretch foil.
Storage:	in covered rooms, on flat surfaces / shelves
	temperature 30 °C, stacking pallet units is not recommended
	protect against sun and weather conditions, keep a distance of at least 1 m from heat sources
Transport:	stacking pallet units is not recommended
	protection against precipitation, deformation, dirt and movement

ADDITIONAL INFORMATION

- The obligation to validate and confirm the compatibility of the product in the technological process, the logistics chain and in terms of compliance with the filled medium rests with the recipient.

Edition: 2

Modification Date: 10.04.2026