



PRODUCT TECHNICAL DATA SHEET

Canister K-10NW

BASIC DATA

Nominal Capacity:	10 L	Application:	industrial chemistry
Thread Standards:	Fi 52, FI 60		household chemistry
Material Options:	HDPE ≥ 97% / dye ≤ 3%		agro sector

AVAILABLE VARIANTS

Parameter	Value	Certificates	Visibility Strip:	available
Weight:	520, 560 g	UN (II i III, to 1,4 g/cm³)	Touch Sign:	available
Colors:	white, colorless, other to be agreed with our employee		IML Label:	not available
Seal Type:	foam-PE		Printing:	not available
			Customer Logo:	available
			Seal Type:	breaking teeth
			Thread Type:	Ø52, Ø60

DIMENSIONS

Parameter	Value	Notes	Parameter	Value	Notes
Weight:	520 g	+10 g	Length:	228 mm	-5/+7 mm
	560 g	+10 g	Width:	192 mm	±2 mm
Label Area:	158(H) x 165(W) mm		Height:	330 mm	+2/-4 mm

AVAILABLE CLOSURES

Suway Ø52 9-11 Nm, SK 60/31BERICAP - 19Nm

PALLETIZATION AND STORAGE - EMPTY PACKAGES

Packaging System No.:	ST21P147	Pallet:	1200x800 mm
Label Content:	manufacturer's name, production date	Spacers:	cardboard trays
	product type, product quantity (pcs)	Pallet Module:	7 layers, stretch foil
	batch number, quality mark	Quantity per layer:	21 pcs
Storage:	protect against sunlight and weather conditions	Quantity per pallet:	147 pcs
	min. 1m away from heat sources	Pallet Weight:	100 kg
	ambient temperature up to 40°C	Pallet Height:	2,5 m
Shelf Life:	12 months from delivery	Seasoning before Filling:	min. 10 h at temp. 16-25°C
Filling Temperature:	max. 40°C		

TRANSPORT - EMPTY PACKAGES

Transport:	protection against rain, deformation, contamination and shifting
Warning:	additional loading of transport modules is not permitted
Layer Arrangement:	



STORAGE AND TRANSPORT - FILLED PACKAGING

Completing: The packaging manufacturer recommends stacking filled canisters in a maximum of three layers, using cardboard dividers on each layer. Completed filled canisters should be wrapped in stretch foil.

Storage: in covered rooms, on flat surfaces / shelves

temperature 40 °C, stacking pallet units is not recommended

protect against sun and weather conditions, keep a distance of at least 1 m from heat sources

Transport: stacking pallet units is not recommended

protection against precipitation, deformation, dirt and movement

ADDITIONAL INFORMATION

- The obligation to validate and confirm the compatibility of the product in the technological process, the logistics chain and in terms of compliance with the filled medium rests with the recipient.

Edition: 2

Modification Date: 10.04.2026